

Product Overview

The NSI833x and NSI834xx devices are high reliability triple/quad-channel digital isolators. The NSI833x and NSI834xx device is safety certified by UL1577 and supports 5kV_{rms} insulation withstand voltage, while providing high electromagnetic immunity and low emissions at low power consumption. The data rate of the NSI833x and NSI834xx is up to 100Mbps, and the common-mode transient immunity (CMTI) is up to 200kV/μs. The NSI833x and NSI834xx device provides digital channel direction configuration and the default output level configuration when the input power is lost. Wide supply voltage of the NSI833x and NSI834xx device supports direct connection to most digital interfaces, making level shifting easy. High system level EMC performance enhance reliability and stability of use. AEC-Q100 (Grade 1) option is provided for all devices.

Key Features

- Up to 5000V_{rms} Insulation voltage
- Data rate: DC to 100Mbps
- Power supply voltage: 2.5V to 5.5V
- High CMTI: 200kV/μs
- Chip level ESD: HBM: ±8kV
- Robust Electromagnetic Compatibility (EMC)
 - System-Level ESD, EFT, and Surge Immunity
 - Low Emissions
- Default output high level or low-level option
- Low power consumption: 1.5mA/ch (1 Mbps)
- Low propagation delay: <18ns
- Operation temperature: -40°C~125°C
- RoHS-compliant packages:
 - SOP16(300mil)

Safety Regulatory Approvals

- UL recognition: up to 5000V_{rms} for 1 minute per UL1577
- CQC certification per GB4943.1
- CSA component notice 5A
- DIN EN IEC 60747-17 (VDE 0884-17)

Applications

- Industrial automation system
- Isolated SPI, RS232, RS485
- General-purpose multichannel isolation
- Motor control

Device Information

Part Number	Package	Body Size
NSI834xWx-Q1SWR	SOP16(300mil)	10.30mm × 7.50mm
NSI833xWx-Q1SWR	SOP16(300mil)	10.30mm × 7.50mm

Functional Block Diagrams




Figure 1. NSI833x Block Diagram




Figure 2. NSI834x Block Diagram

INDEX

1. PIN CONFIGURATION AND FUNCTIONS	3
2. ABSOLUTE MAXIMUM RATINGS	5
3. ESD RATINGS	5
4. RECOMMENDED OPERATING CONDITIONS	6
5. THERMAL INFORMATION	6
6. SPECIFICATIONS	6
6.1. ELECTRICAL CHARACTERISTICS	6
6.2. SUPPLY CURRENT CHARACTERISTICS – 5V SUPPLY	7
6.3. SUPPLY CURRENT CHARACTERISTICS –3.3V SUPPLY	9
6.4. SUPPLY CURRENT CHARACTERISTICS–2.5V SUPPLY	12
6.5. SWITCHING CHARACTERISTICS - 5V SUPPLY	14
6.6. SWITCHING CHARACTERISTICS - 3.3V SUPPLY	14
6.7. SWITCHING CHARACTERISTICS - 2.5V SUPPLY	15
6.8. TYPICAL PERFORMANCE CHARACTERISTICS	16
6.9. PARAMETER MEASUREMENT INFORMATION	18
7. HIGH VOLTAGE FEATURE DESCRIPTION	19
7.1. INSULATION AND SAFETY RELATED SPECIFICATIONS	19
7.2. INSULATION CHARACTERISTICS	19
7.3. SAFETY-LIMITING VALUES	21
7.4. REGULATORY INFORMATION	22
8. FUNCTION DESCRIPTION	23
8.1. OVERVIEW	23
8.2. OOK MODULATION	24
9. APPLICATION NOTE	25
9.1. TYPICAL APPLICATION CIRCUIT	25
9.2. PCB LAYOUT	26
9.3. HIGH SPEED PERFORMANCE	26
9.4. TYPICAL SUPPLY CURRENT EQUATIONS	27
10. PACKAGE INFORMATION	28
11. ORDER INFORMATION	29
12. TAPE AND REEL INFORMATION	30
13. REVISION HISTORY	32

1. Pin Configuration and Functions




Figure 1.1 NSI8330 Package




Figure 1.2 NSI8331 Package

Table 1.1 NSI833x Pin Configuration and Description

NSI8330 PIN NO.	NSI8331 PIN NO.	SYMBOL	FUNCTION
1	1	VDD ₁	Power Supply for Isolator Side 1
2	2	GND ₁	Ground 1, the ground reference for Isolator Side 1
3	3	INA	Logic Input A
4	4	INB	Logic Input B
5	12	INC	Logic Input C
6	6	NC	No Connection.
7	7	NC /EN ₁	No connection (NSI8330) Or output Enable 1 (NSI8331). Active high logic input. When EN ₁ is high or NC, the output of Side 1 is enabled. When EN ₁ is low, the output of Side 1 is disabled to high impedance state.
8	8	GND ₁	Ground 1, the ground reference for Isolator Side 1
9	9	GND ₂	Ground 2, the ground reference for Isolator Side 2
10	10	EN ₂	Output Enable 2. Active high logic input. When EN ₂ is high or NC, the output of Side 2 is enabled. When EN ₂ is low, the output of Side 2 is disabled to high impedance state.
11	11	NC	No Connection.
12	5	OUTC	Logic Output C
13	13	OUTB	Logic Output B
14	14	OUTA	Logic Output A
15	15	GND ₂	Ground 2, the ground reference for Isolator Side 2
16	16	VDD ₂	Power Supply for Isolator Side 2




Figure 1.3 NSI8340 Package

Figure 1.4 NSI8341 Package

Figure 1.5 NSI8342 Package

Table 1.2 NSI834x Pin Configuration and Description

NSI8340 PIN NO.	NSI8341 PIN NO.	NSI8342 PIN NO.	SYMBOL	FUNCTION
1	1	1	VDD ₁	Power Supply for Isolator Side 1
2	2	2	GND ₁	Ground 1, the ground reference for Isolator Side 1
3	3	3	INA	Logic Input A
4	4	4	INB	Logic Input B
5	5	12	INC	Logic Input C
6	11	11	IND	Logic Input D
7	7	7	NC/EN ₁	No Connection (NSI8340). Or Output Enable 1 (NSI8341/2). Active high logic input. When EN ₁ is high or NC, the output of Side 1 is enabled. When EN ₁ is low, the output of Side 1 is disabled to high impedance state.
8	8	8	GND ₁	Ground 1, the ground reference for Isolator Side 1
9	9	9	GND ₂	Ground 2, the ground reference for Isolator Side 2
10	10	10	EN ₂	Output Enable 2. Active high logic input. When EN ₂ is high or NC, the output of Side 2 is enabled. When EN ₂ is low, the output of Side 2 is disabled to high impedance state.
11	6	6	OUTD	Logic Output D
12	12	5	OUTC	Logic Output C
13	13	13	OUTB	Logic Output B
14	14	14	OUTA	Logic Output A
15	15	15	GND ₂	Ground 2, the ground reference for Isolator Side 2
16	16	16	VDD ₂	Power Supply for Isolator Side 2

2. Absolute Maximum Ratings

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Power Supply Voltage	VDD1, VDD2	-0.5		6.5	V	
Maximum Input Voltage	VINA, VINB, VINC, VIND	-0.4		VDD+0.4	V	The maximum voltage must not exceed 6.5V
Maximum Output Voltage	VOUTA, VOUTB, VOUTC, VOUTD	-0.4		VDD+0.4	V	The maximum voltage must not exceed 6.5V
Maximum Input/Output Pulse Voltage	VINA, VINB, VINC, VIND, VOUTA, VOUTB, VOUTC, VOUTD	-0.8		VDD+0.8	V	Pulse width should be less than 100ns, and the duty cycle should be less than 10%
Output current	I _o	-15		15	mA	
Operating Temperature	T _{opr}	-40		125	°C	
Junction Temperature	T _j			150	°C	
Storage Temperature	T _{stg}	-65		150	°C	

- (1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating conditions. Exposure to Absolute Maximum Rated conditions for extended periods may affect device reliability.
- (2) Power supply voltage and input/output voltage are respect to the local ground terminal (GND1 or GND2) voltage values.

3. ESD Ratings

Parameters	Ratings	Value	Unit
Electrostatic discharge (ESD)	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽²⁾	±8000	V
	Charged device model (CDM), per JEDEC specification JESD22-C101 ⁽³⁾	±2000	V

- (1) Though this device features proprietary protection circuitry, proper ESD precautions should be considered to avoid performance degradation of damage due to high energy ESD event. Charged devices and circuit boards may discharge without detection.
- (2) Safe manufacturing requires 500-V HBM and standard ESD precautions, per JEDEC document JEP155.
- (3) Safe manufacturing requires 250-V CDM and standard ESD precautions, per JEDEC document JEP157.

4. Recommended Operating Conditions

Parameters	Symbol	min	typ	max	unit
Power Supply Voltage	VDD1, VDD2	2.5		5.5	V
Operating Temperature	T _{opr}	-40		125	°C
High Level Input Voltage	V _{IH}	2			V
Low Level Input Voltage	V _{IL}			0.8	V
Data rate	DR			100	Mbps

5. Thermal Information

Parameters	Symbol	SOP16(300mil)	Unit
IC Junction-to-Air Thermal Resistance	R _{θJA}	78.9	°C/W
Junction-to-case (top) thermal resistance	R _{θJC (top)}	41.6	°C/W
Junction-to-board thermal resistance	R _{θJB}	43.6	°C/W
Junction-to-top characterization parameter	Ψ _{JT}	7.0	°C/W
Junction-to-board characterization parameter	Ψ _{JB}	23.0	°C/W

6. Specifications

6.1. Electrical Characteristics

(VDD1=2.5V~5.5V, VDD2=2.5V~5.5V, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at VDD1 = 5V, VDD2 = 5V, Ta = 25°C)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Power on Reset	VDD _{POR} ⁽¹⁾	2	2.2	2.4	V	POR threshold as during power-up
	VDD _{HYS} ⁽¹⁾		0.1		V	POR threshold Hysteresis
Rising input switching threshold	V _{IT+} ⁽¹⁾		1.5	2	V	
Falling input switching threshold	V _{IT-} ⁽¹⁾	0.8	1.15		V	
Input threshold voltage hysteresis	V _{IT_HYS} ⁽¹⁾		0.35		V	

High Level Output Voltage	V _{OH}	VDD-0.4			V	I _{OH} = -4mA
Low Level Output Voltage	V _{OL}			0.4	V	I _{OL} = 4mA
Output Impedance	R _{out} ⁽¹⁾		50		ohm	
Input Pull high or low Current	I _{pull}		5	10	μA	
Start Up Time after POR	tr _{bs} ⁽²⁾		22	32	μs	
Common Mode Transient Immunity	CMTI	±150	±200		kV/μs	See Figure 6.11 , C _L = 15pF

⁽¹⁾ Not test covered, guaranteed by characterization.

⁽²⁾ Not test covered, guaranteed by design.

6.2. Supply Current Characteristics – 5V Supply

(VDD1=5V± 10%, VDD2=5V± 10%, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at **VDD1 = 5V, VDD2 = 5V, Ta = 25°C**)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Supply current	NSI8340					
	I _{DD1} (Q0)		1.48	1.74	mA	All Input 0V for NSI8340x0 Or All Input at supply for NSI8340x1
	I _{DD2} (Q0)		4.28	5.10	mA	
	I _{DD1} (Q1)		6.20	7.44	mA	All Input at supply for NSI8340x0 Or All Input 0V for NSI8340x1
	I _{DD2} (Q1)		4.30	5.14	mA	
	I _{DD1} (1M)		3.93	4.71	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		4.37	5.29	mA	
	I _{DD1} (10M)		4.16	5.20	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		5.80	7.00	mA	
	I _{DD1} (100M)		4.77	5.95	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		26.39	32.99	mA	
	NSI8341					
	I _{DD1} (Q0)		2.18	2.58	mA	All Input 0V for NSI8341x0 Or All Input at supply for NSI8341x1
	I _{DD2} (Q0)		3.58	4.26	mA	
	I _{DD1} (Q1)		5.72	6.86	mA	All Input at supply for NSI8341x0 Or All Input 0V for NSI8341x1
	I _{DD2} (Q1)		4.77	5.71	mA	
	I _{DD1} (1M)		4.04	4.85	mA	All Input with 1Mbps,

Parameters	Symbol	Min	Typ	Max	Unit	Comments
	I _{DD2} (1M)		4.26	5.14	mA	C _L =15pF
	I _{DD1} (10M)		4.57	5.65	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		5.39	6.55	mA	
	I _{DD1} (100M)		10.17	12.71	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		20.98	26.23	mA	
	NSI8342					
	I _{DD1} (Q0)		2.88	3.42	mA	All Input 0V for NSI8342x0 Or All Input at supply for NSI8342x1
	I _{DD2} (Q0)		2.88	3.42	mA	
	I _{DD1} (Q1)		5.25	6.29	mA	All Input at supply for NSI8342x0 Or All Input 0V for NSI8342x1
	I _{DD2} (Q1)		5.25	6.29	mA	
	I _{DD1} (1M)		4.15	5.00	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		4.15	5.00	mA	
	I _{DD1} (10M)		4.98	6.10	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.98	6.10	mA	
	I _{DD1} (100M)		15.58	19.47	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		15.58	19.47	mA	

Parameters	Symbol	Min	Typ.	Max	Unit	Comments
Supply current	NSI8330					
	I _{DD1} (Q0)		1.40	1.78	mA	All Input 0V for NSI8330x0 Or All Input at supply for NSI8330x1
	I _{DD2} (Q0)		4.14	5.03	mA	
	I _{DD1} (Q1)		4.94	5.99	mA	All Input at supply for NSI8330x0 Or All Input 0V for NSI8330x1
	I _{DD2} (Q1)		4.15	5.06	mA	
	I _{DD1} (1M)		3.24	3.94	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		4.20	5.17	mA	
	I _{DD1} (10M)		3.41	4.31	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		5.28	6.45	mA	
	I _{DD1} (100M)		3.87	4.87	mA	All Input with 100Mbps, C _L =15pF
	I _{DD2} (100M)		20.72	25.95	mA	
	NSI8331					
	I _{DD1} (Q0)		2.74	3.35	mA	All Input 0V for NSI8331x0 Or All Input at supply for NSI8331x1
	I _{DD2} (Q0)		2.80	3.39	mA	
	I _{DD1} (Q1)		5.10	6.21	mA	All Input at supply for NSI8331x0 Or All Input 0V for NSI8331x1
	I _{DD2} (Q1)		3.99	4.84	mA	
	I _{DD1} (1M)		3.98	4.88	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.46	4.23	mA	
	I _{DD1} (10M)		4.46	5.55	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.23	5.21	mA	
	I _{DD1} (100M)		9.91	12.43	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		14.68	18.39	mA	

6.3. Supply Current Characteristics –3.3V Supply

(VDD1=3.3V± 10%, VDD2=3.3V± 10%, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at VDD1 = 3.3V, VDD2 = 3.3V, Ta = 25°C)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Supply current	NSI8340					
	I _{DD1} (Q0)		1.19	1.68	mA	All Input 0V for NSI8340x0 Or All Input at supply for NSI8340x1
	I _{DD2} (Q0)		3.93	5.00	mA	

Parameters	Symbol	Min	Typ	Max	Unit	Comments
	I _{DD1} (Q1)		5.84	7.30	mA	All Input at supply for NSI8340x0 Or All Input 0V for NSI8340x1
	I _{DD2} (Q1)		3.94	5.04	mA	
	I _{DD1} (1M)		3.58	4.60	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.98	5.12	mA	
	I _{DD1} (10M)		3.82	5.09	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.92	6.27	mA	
	I _{DD1} (100M)		4.94	5.92	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		17.08	20.50	mA	
	NSI8341					
	I _{DD1} (Q0)		1.87	2.51	mA	All Input 0V for NSI8341x0 Or All Input at supply for NSI8341x1
	I _{DD2} (Q0)		3.24	4.17	mA	
	I _{DD1} (Q1)		5.36	6.73	mA	All Input at supply for NSI8341x0 Or All Input 0V for NSI8341x1
	I _{DD2} (Q1)		4.41	5.60	mA	
	I _{DD1} (1M)		3.68	4.73	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.88	4.99	mA	
	I _{DD1} (10M)		4.09	5.38	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.64	5.97	mA	
	I _{DD1} (100M)		7.97	9.56	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		14.04	16.85	mA	
	NSI8342					
	I _{DD1} (Q0)		2.56	3.34	mA	All Input 0V for NSI8342x0 Or All Input at supply for NSI8342x1
	I _{DD2} (Q0)		2.56	3.34	mA	
	I _{DD1} (Q1)		4.89	6.17	mA	All Input at supply for NSI8342x0 Or All Input 0V for NSI8342x1
	I _{DD2} (Q1)		4.89	6.17	mA	
	I _{DD1} (1M)		3.78	4.86	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.78	4.86	mA	
	I _{DD1} (10M)		4.37	5.68	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.37	5.68	mA	
I _{DD1} (100M)		11.00	13.21	mA	All Input with 100Mbps,	

Parameters	Symbol	Min	Typ	Max	Unit	Comments
	I _{DD2} (100M)		11.00	13.21	mA	C _L = 15pF

Parameters	Symbol	Min	Typ.	Max	Unit	Comments
Supply current	NSI8330					
	I _{DD1} (Q0)		1.18	1.68	mA	All Input 0V for NSI8330x0 Or All Input at supply for NSI8330x1
	I _{DD2} (Q0)		3.87	4.95	mA	
	I _{DD1} (Q1)		4.67	5.88	mA	All Input at supply for NSI8330x0 Or All Input 0V for NSI8330x1
	I _{DD2} (Q1)		3.94	4.98	mA	
	I _{DD1} (1M)		2.98	3.86	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.91	5.04	mA	
	I _{DD1} (10M)		3.15	4.22	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.61	5.90	mA	
	I _{DD1} (100M)		3.99	4.85	mA	All Input with 100Mbps, C _L =15pF
	I _{DD2} (100M)		13.73	16.58	mA	
	NSI8331					
	I _{DD1} (Q0)		2.56	3.29	mA	All Input 0V for NSI8331x0 Or All Input at supply for NSI8331x1
	I _{DD2} (Q0)		2.56	3.33	mA	
	I _{DD1} (Q1)		4.83	6.11	mA	All Input at supply for NSI8331x0 Or All Input 0V for NSI8331x1
	I _{DD2} (Q1)		3.72	4.75	mA	
	I _{DD1} (1M)		3.71	4.78	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.18	4.12	mA	
	I _{DD1} (10M)		4.06	5.31	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		3.70	4.81	mA	
	I _{DD1} (100M)		7.66	9.29	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		10.06	12.14	mA	

6.4. Supply Current Characteristics–2.5V Supply

(VDD1=2.5V± 10%, VDD2=2.5V± 10%, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at VDD1 = 2.5V, VDD2 = 2.5V, Ta = 25°C)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Supply current	NSI8340					
	I _{DD1} (Q0)		1.17	1.64	mA	All Input 0V for NSI8340x0 Or All Input at supply for NSI8340x1
	I _{DD2} (Q0)		3.71	4.82	mA	
	I _{DD1} (Q1)		5.74	6.87	mA	All Input at supply for NSI8340x0 Or All Input 0V for NSI8340x1
	I _{DD2} (Q1)		3.86	5.03	mA	
	I _{DD1} (1M)		3.50	4.21	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.86	5.13	mA	
	I _{DD1} (10M)		3.68	4.88	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.56	5.82	mA	
	I _{DD1} (100M)		4.66	5.63	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		13.58	16.29	mA	
	NSI8341					
	I _{DD1} (Q0)		1.80	2.43	mA	All Input 0V for NSI8341x0 Or All Input at supply for NSI8341x1
	I _{DD2} (Q0)		3.07	4.02	mA	
	I _{DD1} (Q1)		5.27	6.41	mA	All Input at supply for NSI8341x0 Or All Input 0V for NSI8341x1
	I _{DD2} (Q1)		4.33	5.49	mA	
	I _{DD1} (1M)		3.59	4.44	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.77	4.90	mA	
	I _{DD1} (10M)		3.90	5.11	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.34	5.58	mA	
	I _{DD1} (100M)		6.89	8.29	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		11.35	13.62	mA	
	NSI8342					
	I _{DD1} (Q0)		2.44	3.23	mA	All Input 0V for NSI8342x0 Or All Input at supply for NSI8342x1
	I _{DD2} (Q0)		2.44	3.23	mA	
	I _{DD1} (Q1)		4.80	5.95	mA	All Input at supply for NSI8342x0 Or All Input 0V for NSI8342x1
	I _{DD2} (Q1)		4.80	5.95	mA	
	I _{DD1} (1M)		3.68	4.67	mA	All Input with 1Mbps,

Parameters	Symbol	Min	Typ	Max	Unit	Comments
	I _{DD2} (1M)		3.68	4.67	mA	C _L =15pF
	I _{DD1} (10M)		4.12	5.35	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.12	5.35	mA	
	I _{DD1} (100M)		9.12	10.96	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		9.12	10.96	mA	

Parameters	Symbol	Min	Typ.	Max	Unit	Comments
Supply current	NSI8330					
	I _{DD1} (Q0)		1.17	1.64	mA	All Input 0V for NSI8330x0 Or All Input at supply for NSI8330x1
	I _{DD2} (Q0)		3.71	4.82	mA	
	I _{DD1} (Q1)		4.60	5.56	mA	All Input at supply for NSI8330x0 Or All Input 0V for NSI8330x1
	I _{DD2} (Q1)		3.82	4.98	mA	
	I _{DD1} (1M)		2.92	3.57	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.82	5.05	mA	
	I _{DD1} (10M)		3.05	4.07	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		4.35	5.57	mA	
	I _{DD1} (100M)		3.79	4.63	mA	All Input with 100Mbps, C _L =15pF
	I _{DD2} (100M)		11.11	13.42	mA	
	NSI8331					
	I _{DD1} (Q0)		2.44	3.23	mA	All Input 0V for NSI8331x0 Or All Input at supply for NSI8331x1
	I _{DD2} (Q0)		2.44	3.23	mA	
	I _{DD1} (Q1)		4.76	5.90	mA	All Input at supply for NSI8331x0 Or All Input 0V for NSI8331x1
	I _{DD2} (Q1)		3.66	4.64	mA	
	I _{DD1} (1M)		3.64	4.59	mA	All Input with 1Mbps, C _L =15pF
	I _{DD2} (1M)		3.10	4.03	mA	
	I _{DD1} (10M)		3.91	5.10	mA	All Input with 10Mbps, C _L =15pF
	I _{DD2} (10M)		3.49	4.54	mA	
	I _{DD1} (100M)		6.65	8.09	mA	All Input with 100Mbps, C _L = 15pF
	I _{DD2} (100M)		8.25	9.96	mA	

6.5. Switching Characteristics - 5V Supply

(VDD1=5V± 10%, VDD2=5V± 10%, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at **VDD1 = 5V, VDD2 = 5V, Ta = 25°C**)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Data Rate	DR	0		100	Mbps	
Minimum Pulse Width	PW			8.3	ns	
Propagation Delay	t _{PLH}		12.0	18	ns	See Figure 6.13 , C _L = 15pF
	t _{PHL}		12.5	18	ns	See Figure 6.13 , C _L = 15pF
Pulse Width Distortion t _{PHL} - t _{PLH}	PWD			5.0	ns	See Figure 6.13 , C _L = 15pF
Rising Time	t _r			5.0	ns	See Figure 6.13 , C _L = 15pF
Falling Time	t _f			5.0	ns	See Figure 6.13 , C _L = 15pF
Peak Eye Diagram Jitter	t _{JIT(PK)}		2.5		ns	
Channel-to-Channel Delay Skew	t _{SK(c2c)}			2.5	ns	
Part-to-Part Delay Skew	t _{SK(p2p)}			5.0	ns	
Disable high to Tri-State	t _{PHZ}		8.67	30	ns	See Figure 6.14 , C _L = 15pF, R _L =1k
Enable to Data high Valid	t _{PZH}		8.75	30	ns	See Figure 6.14 , C _L = 15pF, R _L =1k
Disable low to Tri-State	t _{PLZ}		7.7	30	ns	See Figure 6.14 , C _L = 15pF, R _L =1k
Enable to Data low Valid	t _{PZL}		9.5	30	ns	See Figure 6.14 , C _L = 15pF, R _L =1k

6.6. Switching Characteristics - 3.3V Supply

(VDD1=3.3V± 10%, VDD2=3.3V± 10%, Ta=-40°C to 125°C. Unless otherwise noted, Typical values are at **VDD1 = 3.3V, VDD2 = 3.3V, Ta = 25°C**)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Data Rate	DR	0		100	Mbps	
Minimum Pulse Width	PW			8.3	ns	
Propagation Delay	t _{PLH}		12.85	19	ns	See Figure 6.13 , C _L = 15pF
	t _{PHL}		12.60	19	ns	See Figure 6.13 , C _L = 15pF
Pulse Width Distortion t _{PHL} - t _{PLH}	PWD			5.0	ns	See Figure 6.13 , C _L = 15pF

Rising Time	t_r			5.0	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Falling Time	t_f			5.0	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Peak Eye Diagram Jitter	$t_{JIT(PK)}$		2.5		ns	
Channel-to-Channel Delay Skew	$t_{SK(c2c)}$			2.5	ns	
Part-to-Part Delay Skew	$t_{SK(p2p)}$			5.0	ns	
Disable high to Tri-State	t_{PHZ}		11	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Enable to Data high Valid	t_{PZH}		11.5	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Disable low to Tri-State	t_{PLZ}		9.3	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Enable to Data low Valid	t_{PZL}		12.3	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$

6.7. Switching Characteristics - 2.5V Supply

($V_{DD1}=2.5\text{V} \pm 10\%$, $V_{DD2}=2.5\text{V} \pm 10\%$, $T_a=-40^\circ\text{C}$ to 125°C . Unless otherwise noted, Typical values are at **$V_{DD1} = 2.5\text{V}$** , **$V_{DD2} = 2.5\text{V}$** , $T_a = 25^\circ\text{C}$)

Parameters	Symbol	Min	Typ	Max	Unit	Comments
Data Rate	DR	0		100	Mbps	
Minimum Pulse Width	PW			8.3	ns	
Propagation Delay	t_{PLH}		13.97	20	ns	See Figure 6.13 , $C_L = 15\text{pF}$
	t_{PHL}		12.72	20	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Pulse Width Distortion $ t_{PHL} - t_{PLH} $	PWD			5.0	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Rising Time	t_r			5.0	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Falling Time	t_f			5.0	ns	See Figure 6.13 , $C_L = 15\text{pF}$
Peak Eye Diagram Jitter	$t_{JIT(PK)}$		2.5		ns	
Channel-to-Channel Delay Skew	$t_{SK(c2c)}$			2.5	ns	
Part-to-Part Delay Skew	$t_{SK(p2p)}$			5.0	ns	
Disable high to Tri-State	t_{PHZ}		13.9	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Enable to Data high Valid	t_{PZH}		15.6	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Disable low to Tri-State	t_{PLZ}		12.6	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$
Enable to Data low Valid	t_{PZL}		16.8	30	ns	See Figure 6.14 , $C_L = 15\text{pF}$, $R_L=1\text{k}$

6.8. Typical Performance Characteristics




Figure 6.1 NSI8340 VDD1 Supply Current vs Data Rate




Figure 6.2 NSI8340 VDD2 Supply Current vs Data Rate




Figure 6.3 NSI8341 VDD1 Supply Current vs Data Rate




Figure 6.4 NSI8341 VDD2 Supply Current vs Data Rate




Figure 6.5 NSI8342 VDD1 Supply Current vs Data Rate




Figure 6.6 NSI8342 VDD2 Supply Current vs Data Rate




Figure 6.7 NSI8330 VDD1 Supply Current vs Data Rate




Figure 6.8 NSI8330 VDD2 Supply Current vs Data Rate




Figure 6.9 NSI8331 VDD1 Supply Current vs Data Rate




Figure 6.10 NSI8331 VDD2 Supply Current vs Data Rate




Figure 6.11 Rising Edge Propagation Delay Vs Temp





Figure 6.12 Falling Edge Propagation Delay Vs Temp

6.9. Parameter Measurement Information



(1) Input Generator Characteristics : PRR $\leq$ 50kHz, $t_r \leq$ 3ns, $t_f \leq$ 3ns, Duty cycle = 50%, $Z_o = 50 \Omega$.

Figure 6.13 Switching Characteristics Test Circuit and Waveform




Figure 6.14 Enable/Disable Propagation Delay Time Test Circuit and Waveform




Figure 6.15 Common-Mode Transient Immunity Test Circuit

7. High Voltage Feature Description

7.1. Insulation and Safety Related Specifications

Parameters	Symbol	Value		Comments
		SOP16 (300mil)	Unit	
Minimum External Clearance	CLR	8	mm	IEC 60664-1
Minimum External Creepage	CPG	8	mm	IEC 60664-1
Distance Through Insulation	DTI	24	µm	Distance through insulation
Tracking Resistance (Comparative Tracking Index)	CTI	>600	V	DIN EN 60112 (VDE 0303-11); IEC 60112
Material Group		I		IEC 60664-1

Description	Test Condition	Value	
		SOP16 (300mil)	
Overvoltage Category per IEC60664-1	For Rated Mains Voltage $\leq$ 150Vrms	I to IV	
	For Rated Mains Voltage $\leq$ 300Vrms	I to IV	
	For Rated Mains Voltage $\leq$ 600Vrms	I to IV	
	For Rated Mains Voltage $\leq$ 1000Vrms	I to III	
Climatic Classification		40/125/21	
Pollution Degree per DIN VDE 0110		2	

7.2. Insulation Characteristics

Description	Test Condition	Symbol	Value	
			SOP16 (300mil)	Unit
Maximum repetitive isolation voltage		V_{IORM}	2121	V_{PEAK}
Maximum working isolation voltage	AC Voltage	V_{IOWM}	1500	V_{RMS}
	DC Voltage		2121	V_{DC}

Description	Test Condition	Symbol	Value	
			SOP16 (300mil)	Unit
Apparent Charge	Method a, after Input/output safety test subgroup 2/3, $V_{ini}=V_{IOTM}$, $t_{ini} = 60s$, $V_{pd(m)}=1.2*V_{IORM}$, $t_m=10s$.	q_{pd}	<5	pC
	Method a, after environmental tests subgroup 1, $V_{ini}=V_{IOTM}$, $t_{ini}=60s$, $V_{pd(m)}=1.6*V_{IORM}$, $t_m=10s$			pC
	Method b, routine test (100% production) and preconditioning (type test); $V_{ini}=1.2*V_{IOTM}$, $t_{ini}=1s$ $V_{pd(m)}=1.875*V_{IORM}$, $t_m=1s$ (method b1) or $V_{pd(m)}=V_{ini}$, $t_m=t_{ini}$ (method b2)			pC
Apparent Charge	Method a, after Input/output safety test subgroup 2/3, $V_{ini}=V_{IOTM}$, $t_{ini} = 60s$, $V_{pd(m)}=1.2*V_{IORM}$, $t_m=10s$.	q_{pd}	\	pC
	Method a, after environmental tests subgroup 1, $V_{ini}=V_{IOTM}$, $t_{ini}=60s$, $V_{pd(m)}=1.3*V_{IORM}$, $t_m=10s$			pC
	Method b, routine test (100% production) and preconditioning (type test); $V_{ini}=1.2*V_{IOTM}$, $t_{ini}=1s$ $V_{pd(m)}=1.5*V_{IORM}$, $t_m=1s$ (method b1) or $V_{pd(m)}=V_{ini}$, $t_m=t_{ini}$ (method b2)			pC
Maximum transient isolation voltage	$t = 60 \text{ sec}$	V_{IOTM}	8000	V_{PEAK}
Maximum impulse voltage	Tested in air, 1.2/50 μs waveform per IEC62368-1	V_{IMP}	6250	V_{PEAK}
Maximum Surge Isolation Voltage	Test method per IEC62368-1, 1.2/50 μs	V_{IOSM}	10000	V_{PEAK}

Description	Test Condition	Symbol	Value	
			SOP16 (300mil)	Unit
	waveform, $V_{IOSM} \geq V_{IMP} \times 1.3$			
Isolation resistance	$V_{IO} = 500V, T_{amb} = 25^{\circ}C$	R_{IO}	$>10^{12}$	Ω
	$V_{IO} = 500V, 100^{\circ}C \leq T_{amb} \leq 125^{\circ}C$	R_{IO}	$>10^{11}$	Ω
	$V_{IO} = 500V, T_{amb} = T_s$	R_{IO}	$>10^9$	Ω
Isolation capacitance	$f = 1MHz$	C_{IO}	0.8	pF
Insulation voltage per UL	$V_{TEST} = V_{ISO}, t = 60s$ (qualification), $V_{TEST} = 1.2 \times V_{ISO}, t = 1s$ (100% production test)	V_{ISO}	5000	V_{RMS}

7.3. Safety-Limiting Values

Reinforced isolation safety-limiting values as outlined in VDE-0884-17 of NSI833x and NSI834x-Q1SWR.

Description	Test Condition	Symbol	Value	Unit
Safety Supply Power	$R_{\theta JA} = 78.9^{\circ}C/W^{1)}$, $T_J = 150^{\circ}C$, $T_A = 25^{\circ}C$		1584	mW
Safety Supply Current	$R_{\theta JA} = 78.9^{\circ}C/W^{1)}$, $V_I = 5V$, $T_J = 150^{\circ}C$, $T_A = 25^{\circ}C$		316.8	mA
Maximum Safety Temperature ²⁾		T_s	150	$^{\circ}C$

- 1) Calculate with the junction-to-air thermal resistance, $R_{\theta JA}$, of SOP16(300mil) package ([Thermal Information Table](#)) which is that of a device installed on a low effective thermal conductivity test board (1s) according to JESD51-3.
- 2) The maximum safety temperature has the same value as the maximum junction temperature (T_J) specified for the device.




Figure 7.1 NSI833x and NSI834x Thermal derating Curve, Dependence of Safety Limiting Values with Case Temperature per DIN EN IEC 60747-17 (VDE 0884-17).

7.4. Regulatory Information

The NSI834xWx-Q1SWR and NSI833xWx-Q1SWR are approved by the organizations listed in table.

<i>UL</i>		<i>CQC</i>	<i>TUV</i>	
UL 1577 Component Recognition Program	Approved under CSA Component Acceptance Notice 5A	Certified according to GB4943.1-2022	DIN EN IEC 60747-17 (VDE 0884-17)	Certified According to EN IEC 62368-1
Single Protection, 5000V _{rms} Isolation voltage	Single Protection, 5000V _{rms} Isolation voltage	Reinforced insulation	Reinforced Insulation V _{IORM} =2121V _{peak} V _{IOTM} =8000V _{peak} V _{IOSM} =10000V _{peak}	5000V _{rms} for 1min
E500602	E500602	CQC20001264939	R 50632560	R 50574061

8. Function Description

8.1. Overview

The NSI833x and NSI834xx is a triple/quad-channel digital isolator based on a capacitive isolation barrier technique. The digital signal is modulated with RF carrier generated by the internal oscillator at the Transmitter side. Then it is transferred through the capacitive isolation barrier and demodulated at the receiver side.

The NSI833x and NSI834xx devices are high reliability triple/quad-channel digital isolators. The NSI833x and NSI834xx device is safety certified by UL1577 and supports 5kV_{rms} insulation withstand voltage while providing high electromagnetic immunity and low emissions at low power consumption. The data rate of the NSI833x and NSI834xx is up to 100Mbps, and the common-mode transient immunity (CMTI) is up to 200kV/μs. The NSI833x and NSI834xx device provides digital channel direction configuration and the default output level configuration when the input power is lost. Wide supply voltage of the NSI833x and NSI834xx device supports connection to most digital interfaces directly, making level shifting easy. High system level EMC performance enhances reliability and stability of use.

The NSI833x and NSI834xx has a default output status when VDD_{IN} is unready and VDD_{OUT} is ready as shown in Table 7.1, which helps with diagnosis when power is missing at the transmitter side. The output B follows the same status as the input A after powering up.

Table 8.1 Output status vs. power status

Input ¹	EN _x ²	VDD _{IN} status	VDD _{OUT} status	Output	Comment
H	H or NC	Ready	Ready	H	Normal operation.
L	H or NC	Ready	Ready	L	
X	L	Ready	Ready	Z	Output Disabled, the output is high impedance (Internal pull up to VDD _{OUT} with NSI833x and NSI834xxx1 or internal pull down to GND with NSI833x and NSI834xxx0)
X	H or NC	Unready	Ready	L(NSI833x and NSI834xxx0) H(NSI833x and NSI834xxx1)	The output follows the same status with the input after input side VDD _{IN} is powered on.
X	L	Unready	Ready	Z	Output Disabled, the output is high impedance (Internal pull up to VDD _{OUT} with NSI833x and NSI834xxx1 or internal pull down to GND with NSI833x and NSI834xxx0)
X	X	Ready	Unready	Undetermined	The output follows the same status with the input after output side VDD _{OUT} is powered on.
Note: H=Logic high; L=Logic low; X=Logic low or logic high; Z=High impedance. VDD_{IN} is input side power; VDD_{OUT} is output side power. (1) There is a protection diode between the input and the VDD_{IN}. When the VDD_{IN} is floating, the strong drive signal through the input pin will put the VDD_{IN} in an indeterminate state. (2) The EN_x is output side enable.					

8.2. OOK Modulation

NSI833x and NSI834x is based on a capacitive isolation barrier technique and the digital signal is modulated with RF carrier generated by the internal oscillator at the transmitter side, as shown in Figure 8.1 to Figure 8.2, then it is transferred through the capacitive isolation barrier and demodulated at the receiver side. The modulation uses OOK modulation technique with key benefits of high noise immunity and low radiation EMI.




Figure 8.1 Single Channel Function Block Diagram




Figure 8.2 OOK Modulation

9. Application Note

9.1. Typical Application Circuit




Figure 9.1 Typical PWM isolation circuit for IPM

9.2. PCB Layout

The NSI833x and NSI834x requires a 0.1 μF bypass capacitor between VDD1 and GND1, VDD2 and GND2. The capacitor should be placed as close as possible to the package. Figure 9.2 to Figure 9.3 show the recommended PCB layout, make sure the space under the chip should keep free from planes, traces, pads and via. To enhance the robustness of a design, the user may also include resistors (50–300 Ω) in series with the inputs and outputs if the system is excessively noisy. The series resistors also improve the system reliability such as latch-up immunity.

The typical output impedance of an isolator driver channel is approximately 50 Ω , $\pm 40\%$. When driving loads where transmission line effects will be a factor, output pins should be appropriately terminated with controlled impedance PCB traces.




Figure 9.2 Recommended PCB Layout — Top Layer



Figure 9.3 Recommended PCB Layout — Bottom Layer

9.3. High Speed Performance

Figure 9.4 shows the eye diagram of NSI833x and NSI834x-Q1 at 50Mbps data rate output. The result shows a typical measurement on NSI833x and NSI834x-Q1 with low jitter and wide open eye characteristics.




Figure9.4 Eye Diagram at 50Mbps PRBS 2¹⁶-1, 2.5V and 25°C

9.4. Typical Supply Current Equations

The typical supply current of NSI834x and NSI833x can be calculated using below equations. I_{DD1} and I_{DD2} are typical supply currents measured in mA, f is data rate measured in Mbps, C_L is the capacitive load measured in pF.

NSI8340:

$$I_{DD1} = 0.298 \cdot a1 + 1.458 \cdot b1 + 0.878 \cdot c1.$$

$$I_{DD2} = 3.93 + 0.5 \cdot VDD2 \cdot f \cdot C_L \cdot c1 \cdot 10^{-3}$$

When $a1$ is the channel number of default state input at side 1, $b1$ is the channel number of non-default state input at side 1, $c1$ is the channel number of switch signal input at side 1.

NSI8341:

$$I_{DD1} = 1.875 + 1.16 \cdot b1 + 0.58 \cdot c1 + 0.5 \cdot VDD1 \cdot f \cdot C_L \cdot c2 \cdot 10^{-3}$$

$$I_{DD2} = 3.245 + 1.16 \cdot b2 + 0.58 \cdot c2 + 0.5 \cdot VDD2 \cdot f \cdot C_L \cdot c1 \cdot 10^{-3}$$

When $b1$ is the channel number of non-default state input at side 1, $c1$ is the channel number of switch signal input at side 1, $b2$ is the channel number of non-default state input at side 2, $c2$ is the channel number of switch signal input at side 2.

NSI8342:

$$I_{DD1} = 2.56 + 1.16 \cdot b1 + 0.58 \cdot c1 + 0.5 \cdot VDD1 \cdot f \cdot C_L \cdot c2 \cdot 10^{-3}$$

$$I_{DD2} = 2.56 + 1.16 \cdot b2 + 0.58 \cdot c2 + 0.5 \cdot VDD2 \cdot f \cdot C_L \cdot c1 \cdot 10^{-3}$$

When $b1$ is the channel number of non-default state input at side 1, $c1$ is the channel number of switch signal input at side 1, $b2$ is the channel number of non-default state input at side 2, $c2$ is the channel number of switch signal input at side 2.

NSI8330:

$$I_{DD1} = 0.298 \cdot a1 + 1.458 \cdot b1 + 0.878 \cdot c1.$$

$$I_{DD2} = 3.93 + 0.5 \cdot VDD2 \cdot f \cdot C_L \cdot c1 \cdot 10^{-3}$$

When $a1$ is the channel number of low input at side 1, $b1$ is the channel number of high input at side 1, $c1$ is the channel number of switch signal input at side 1.

NSI8331:

$$I_{DD1} = 2.56 + 1.16 \cdot b1 + 0.58 \cdot c1 + 0.5 \cdot VDD1 \cdot f \cdot C_L \cdot c2 \cdot 10^{-3}$$

$$I_{DD2} = 2.56 + 1.16 \cdot b2 + 0.58 \cdot c2 + 0.5 \cdot VDD2 \cdot f \cdot C_L \cdot c1 \cdot 10^{-3}$$

When $b1$ is the channel number of non-default state input at side 1, $c1$ is the channel number of switch signal input at side 1, $b2$ is the channel number of non-default state input at side 2, $c2$ is the channel number of switch signal input at side 2.

10. Package Information




Figure 10.1 SOP16(300mil)/SOW16 Package Shape and Dimension in millimeters

NOTE: This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.





Figure 10.2 SOP16(300mil) SOW16 Package Board Layout Example

11. Order Information



Part Number	Isolation Rating (kV)	Number of side 1 inputs	Number of side 2 inputs	Max Data Rate (Mbps)	Default Output State	Temperature	M S L	Package Type	Package Drawing	SPQ	MPQ	Marking
NSI8340W0-Q1SWR	5	4	0	100	Low	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 40W0Q
NSI8340W1-Q1SWR	5	4	0	100	High	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 40W1Q
NSI8341W0-Q1SWR	5	3	1	100	Low	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 41W0Q
NSI8341W1-Q1SWR	5	3	1	100	High	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 41W1Q
NSI8342W0-Q1SWR	5	2	2	100	Low	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 42W0Q
NSI8342W1-Q1SWR	5	2	2	100	High	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 42W1Q
NSI8330W0-Q1SWR	5	3	0	100	Low	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 30W0Q
NSI8330W1-Q1SWR	5	3	0	100	High	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 30W1Q
NSI8331W0-Q1SWR	5	2	1	100	Low	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 31W0Q
NSI8331W1-Q1SWR	5	2	1	100	High	-40 to 125°C	3	SOP16 (300mil)	SOW16	1000	1000	NSi83 31W1Q

NOTE: All packages are RoHS-compliant with peak reflow temperatures of 260 °C according to the JEDEC industry standard classifications and peak solder temperatures.

Part Number Rule:



12. Tape and Reel Information




**ARBOR HOLE
DETAIL A
SCALE: 3:1**

PRODUCT SPECIFICATION						
TAPE WIDTH	$\phi A \pm 2.0$	$\phi N \pm 2.0$	W1	W2 (Max)	W3	E (MIN)
08MM	330	178	$8.4^{+1.5}_{-0.0}$	14.4	SHALL ACCOMMODATE TAPE WIDTH WITHOUT INTERFERENCE	5.5
12MM	330	178	$12.4^{+2.0}_{-0.0}$	18.4		5.5
16MM	330	178	$16.4^{+2.0}_{-0.0}$	22.4		5.5
24MM	330	178	$24.4^{+2.0}_{-0.0}$	30.4		5.5
32MM	330	178	$32.4^{+2.0}_{-0.0}$	38.4		5.5

SURFACE RESISTIVITY			
LEGEND	SR RANGE	TYPE	COLOUR
A	BELOW 10^{12}	ANTISTATIC	ALL TYPES
B	10^6 TO 10^{11}	STATIC DISSIPATIVE	BLACK ONLY
C	10^5 & BELOW 10^5	CONDUCTIVE(GENERIC)	BLACK ONLY
E	10^9 TO 10^{11}	ANTISTATIC(COATED)	ALL TYPES

Figure 13.1 Reel Information (for all packages)



- 1.10 sprocket hole pitch cumulative tolerance ± 0.20 .
2. Carrier camber is within 1 mm in 250 mm.
3. Material : Black Conductive Polystyrene Alloy.
4. All dimensions meet EIA-481 requirements.
5. Thickness: 0.30 ± 0.05 mm.
6. Packing length per 22" reel: 378 Meters.(Rewind N=122)
7. Component load per 13" reel: 1000 pcs.
8. Surface resistivity: $10^5 \sim 10^{10} \Omega/\square$



W	16.00 ± 0.20
A0	10.75 ± 0.10
B0	10.70 ± 0.10
K0	2.80 ± 0.10
K1	2.50 ± 0.10




Figure 13.2 Tape Information of SOP16(300mil)

13. Revision History

Revision	Description	Date
1.0	Initial version	2025/10/10
1.1	Combine NSI833x-Q1 datasheet with NSI834x-Q1	2025/6/10

IMPORTANT NOTICE

The information given in this document (the “Document”) shall in no event be regarded as any warranty or authorization of, express or implied, including but not limited to accuracy, completeness, merchantability, fitness for a particular purpose or infringement of any third party’s intellectual property rights.

Users of this Document shall be solely responsible for the use of NOVOSENSE’s products and applications, and for the safety thereof. Users shall comply with all laws, regulations and requirements related to NOVOSENSE’s products and applications, although information or support related to any application may still be provided by NOVOSENSE.

This Document is provided on an “AS IS” basis, and is intended only for skilled developers designing with NOVOSENSE’s products. NOVOSENSE reserves the rights to make corrections, modifications, enhancements, improvements or other changes to the products and services provided without notice. NOVOSENSE authorizes users to use this Document exclusively for the development of relevant applications or systems designed to integrate NOVOSENSE’s products. No license to any intellectual property rights of NOVOSENSE is granted by implication or otherwise. Using this Document for any other purpose, or any unauthorized reproduction or display of this Document is strictly prohibited. In no event shall NOVOSENSE be liable for any claims, damages, costs, losses or liabilities arising out of or in connection with this Document or the use of this Document.

For further information on applications, products and technologies, please contact NOVOSENSE (www.novosns.com).

Suzhou NOVOSENSE Microelectronics Co., Ltd